



Mobil DTE™ Oil Named Series

Industrial Mobil, United States

Premium Performance Circulating Lubricants

Product Description

The Mobil DTE™ Oil Named Series of lubricants are premium performance circulating lubricants designed for applications including steam and hydro turbine sets and other systems where long lubricant service life is required. Mobil DTE Oil Named Series lubricants are formulated from highly refined base stocks and an additive system which provide an extremely high level of chemical and thermal stability, rapid and complete separation from water and a high resistance to emulsification. They provide excellent protection against rust and corrosion, including resistance to salt water, and good antiwear properties. They have a high viscosity index which ensures minimum variation of film thickness with temperature and minimum power loss during the warm up period. These grades have excellent air release properties which allow entrained air to separate, thus avoiding pump cavitation and erratic operation.

Mobil DTE Oil Named are the lubricants of choice for many users because of their reputation for long life, excellent equipment protection and outstanding versatility in the wide variety of industrial applications. DTE Oil Named lubricants are used widely in steam turbines and hydroturbines with splash, bath and ring-oiling arrangements, and all other continuous circulation methods involving pumps, valves and ancillary equipment. This product series is recommended for continuous service in the lubrication of plain and rolling bearings and parallel shaft gearing. They have also been used successfully in rotary air compressor applications and reciprocating natural gas compressors as well as vacuum pumps. Their reputation is based on many decades of successful service and satisfied users.

Features and Benefits

The Mobil DTE family of products is well known and highly regarded worldwide based on their outstanding performance and the R & D expertise and the global technical support which stand behind the brand. The highly versatile performance of Mobil DTE Oil Named oils has made them the oil of choice for a multitude of industrial equipment applications around the world.

Mobil DTE Named oils enjoy an excellent reputation in the lubrication of the circulation systems of steam turbines and hydro turbines, including geared turbines, plus a wide variety of ancillary equipment. As designs change and increase in severity, it is the challenge of our formulation scientists to understand the effect of these changes on the lubricant and to formulate these products for the broad versatility they are recognised for.

For the Mobil DTE Oil Named Series of lubricants, this process has resulted in the use of special base stocks for outstanding oxidation stability, plus a unique additive combination to ensure the excellent, wide-ranging performance of these oils. A review of the features, advantages and potential benefits of the product are shown below.

Features	Advantages and Potential Benefits
Very high level of chemical and thermal stability and resistance to sludging and varnishing	Long oil change life in circulation systems and reduced oil replacement costs
	Less unplanned downtime and reduced maintenance costs
Excellent water release properties	Improved operating efficiency
Very good antiwear protection	Longer equipment life, reduced maintenance and downtime
Long term protection against rust and corrosion	Longer equipment life, reduced maintenance and downtime
High resistance to foaming and excellent air release	Avoids pump cavitation, noisy and erratic operation
Highly versatile - multiple applications	Rationalize inventory, reduced inventory costs

Applications

The Mobil DTE Oil Named Series of lubricants are premium performance circulating lubricants designed for applications where long lubricant service life is required. Specific applications include:

- Land-based and marine steam turbine, hydro turbine and some gas turbine circulation systems, including pumps, valves and other ancillary equipment
- Continuous service in plain and roller bearings and parallel shaft gearing
- Turbines with oil supplied by splash, bath, ring oiling or other mechanical means
- Moderate severity hydraulic pumps
- Compressors and vacuum pumps handling air, natural gas, and inert gases, and with discharge temperatures not exceeding 150C

Specifications and Approvals

Mobil DTE Named Series meets or exceeds the requirements of:	Mobil DTE Light	Mobil DTE Medium	Mobil DTE Heavy Medium	Mobil DTE Heavy
DIN 51515-1: 2010-02	X	X	X	X
DIN 51517-2: 2009-06	X	X	X	X
GE GEK 46506D	X			

Mobil DTE Named Series meets or exceeds the requirements of:	Mobil DTE Light	Mobil DTE Medium	Mobil DTE Heavy Medium	Mobil DTE Heavy
GE GEK 27070	X			
GE GEK 28143A	X	X		
JIS K-2213 Type 2 w/Additives (1983)	X	X	X	

Typical Properties

Mobil DTE Named Series	Mobil DTE Light	Mobil DTE Medium	Mobil DTE Heavy Medium	Mobil DTE Heavy
ISO Viscosity Grade	32	46	68	100
Viscosity, ASTM D 445				
cSt @ 40° C	31	44.5	65.1	95.1
cSt @ 100° C	5.5	6.9	8.7	10.9
Viscosity Index, ASTM D 2270	102	98	95	92
Pour Point, °C, ASTM D 97	-18	-15	-15	-15
Flash Point, °C, ASTM D 92	218	221	223	237
Density @ 15° C kg/l, ASTM D 4052	0.85	0.86	0.87	0.88
TOST, ASTM D 943, Hours to 2 NN	5000	3700	4500	4500
Rust Prevention, ASTM D 665:				
Distilled Water	Pass	Pass	Pass	Pass
Sea Water	Pass	Pass	Pass	Pass
Water Seperability, ASTM D 1401,Min. to 3 ml emulsion @ 54°C	15	15	20	30
Copper Strip Corrosion, ASTM D 130,3 hrs @ 121° C	1B	1B	1B	1B
Foam Test, ASTM D 892, Seq I Tendency/stability, ml/ml	20/0	50/0	50/0	50/0

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and DTE are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

07-2016

Exxon Mobil Corporation

22777 Springwoods Village Parkway
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

© Copyright 2003-2017 Exxon Mobil Corporation. All Rights Reserved.